



innovative power wizard™ power meter offers unbeatable convenience

accurate The measurement of laser power is quick and simple with our Power Wizard™ power meter. Synrad's hand held Power Wizard™ is a low cost, lightweight alternative to bulky, two-piece thermopile power meters and probes, or traditional "meat thermometer" probes. Ideally suited for industrial, scientific, and medical applications, use it when setting up your system, and as a service tool to ensure maximum performance of your laser system at any time.

laser
power
measurement

in a
compact
package

Designed to measure power levels from 1 - 250W, Synrad's Power Wizard™ measures output power from the ultraviolet to the far infrared. This makes it the perfect

tool for checking the performance of your excimer, argon, diode, YAG, and CO₂ lasers, to name just a few.

Automatic data hold and auto ranging make the Power Wizard™ easy to use. Simply insert the sensor into the laser beam and hold in place for a few seconds. The easy-to-read LCD screen will then display an accurate measurement of average laser power. To take another reading, simply push the reset button, and the Power Wizard™ is ready to go!

SYNRAD
An Excel Technology Company

Portfolio
Product

Power Wizard™

PW-250 Power Meter

Specifications

Range	1-250W
Resolution	0.1W
Wavelength range ¹	190nm-11µm
Individual calibrated wavelength ¹	10.6µm
Target absorption ¹ , 190nm-1.1µm & 9-11µm	0.96-0.99
Target absorption ¹ , 190nm-1.1µm	0.93-0.99
Accuracy	±5%
Target diameter (mm)	22
Settling time (seconds)	<4
Max. allowable input power (single application, W)	300
Max. average power density ² (kW/cm ²)	20
Max. peak energy density ³ (J/cm ²)	1
Max. target temperature (°C)	180
Typical target temp. rise per measurement (°C/W)	0.4
Typical battery life	5 years 25,000 readings
Battery type	3xCR2025 lithium
Auto shut-off time (seconds)	25
Data hold time (seconds)	15
Size (mm)	159x30x12
Weight (g)	80

Specifications subject to change without notice

¹ Typical absorption curve supplied with each meter.

² Damage to coating may occur above this value.

³ For pulsed lasers and 50µsec pulse width.

Features:

- wavelength range: 190nm - 11µm
- pocket sized
- highly accurate
- instant recycle
- easy-to-read digital display
- automatic data hold
- auto ranging
- automatic shut-off
- long life lithium battery
- audible signals

1.800.SYNRAD1



An Excel Technology Company